

T/S-100I Maintenance-Free Forged Brass Full Port Ball Valve



Maintenance-free design with Dacromet® coated steel handle and nut for greater corrosion resistance. Fully rated ball valve. Available in sizes and configurations 1/8" - 4", FNPT x FNPT and 1/2" - 4", Sweat x Sweat.

- T-100I CSA Certified for use with natural, manufactured, mixed, liquid petroleum, and LP gas air mixtures: 1/2 lb (1/4" - 3"); 2 lb and 5 lb (1/4", 1/2" - 2").
- T-100I ANSI/ASME B16.33 for use in gas piping systems up to 125 psig (1/2" - 1").
- T-100I UL Listed 44R8 for LP, natural and manufactured gases; flammable liquids, #6 oil at 250 deg. F (1/4" - 2").
- T-100I UL Listed 757X for fire protection service (1/2" - 2").
- T-100I Factory Mutual approved for fire protection service (1/2" - 2").

T/S-100INL Maintenance-Free No Lead Forged Brass Full Port Ball Valve



Maintenance-free, dual Viton® O-ring stem design, lighter weight and durable forged no lead brass body, blow-out proof stem, PTFE seats for improved wear. Does not require any additional steps to solder, as compared to traditional brass valves. Suitable for potable water applications. 1/8" - 4", FNPT x FNPT and 1/2" - 4", Sweat x Sweat.

- Third party certified no lead, ANSI/NSF 61-G, NSF.
- T-100INL CSA Certified for use with natural, manufactured, mixed, liquid petroleum, and LP gas/air mixtures: 1/2 lb (1/2" - 3"); 2 lb and 5 lb (1/4", 1/2" - 2").
- T-100INL ANSI/ASME B16.33 for use in gas piping systems up to 125 psig (1/2" - 1").
- T-100INL UL Listed 44R8 for LP, natural and manufactured gases; flammable liquids, #6 oil at 250 deg. F (1/4" - 2").
- T-100INL Factory Mutual approved for fire protection service (1/2" - 2").
- T-100INL UL listed 757X for fire protection service (1/2" - 2").

T/S-100IT Maintenance-Free Forged Brass Full Port Ball Valve with T-Handle



Maintenance-free, dual Viton® O-ring stem design, lighter weight and durable forged traditional brass body, blow-out proof stem, PTFE seats for improved wear. Coated cast aluminum tee handle that is light weight and compact in size. Available in sizes and configurations 1/2" x 1", FNPT x FNPT and 1/2" - 1", Sweat x Sweat.

- T-100IT CSA Certified for use with natural, manufactured, mixed, liquid petroleum, and LP gas/air mixtures: 1/2 lb (1/2" - 3"); 2 lb and 5 lb (1/4", 1/2" - 2").
- T-100IT ANSI/ASME B16.33 for use in gas piping systems up to 125 psig (1/2" - 1").
- T-100IT UL Listed 44R8 for LP, natural and manufactured gases; flammable liquids, #6 oil at 250 deg. F (1/4" - 2").
- T-100IT UL Listed 757X for fire protection service (1/2" - 2").
- T-100IT Factory Mutual approved for fire protection service (1/2" - 2").

T/S-100ITNL Maintenance-Free No Lead Forged Brass Full Port Ball Valve with T-Handle



Maintenance-free, dual Viton® O-ring stem design, lighter weight and durable forged no lead brass body, blow-out proof stem, PTFE seats for improved wear. Coated cast aluminum tee handle that is light weight and compact in size. Available in sizes and configurations 1/2" x 1", FNPT x FNPT and 1/2" - 1", Sweat x Sweat.

- Third party certified no lead, ANSI/NSF 61-G, NSF.
- T-100ITNL CSA Certified for use with natural, manufactured, mixed, liquid petroleum, and LP gas/air mixtures: 1/2 lb (1/2" - 3"); 2 lb and 5 lb (1/4", 1/2" - 2").
- T-100ITNL ANSI/ASME B16.33 for use in gas piping systems up to 125 psig (1/2" - 1").
- T-100ITNL UL Listed 44R8 for LP, natural and manufactured gases; flammable liquids, #6 oil at 250 deg. F (1/4" - 2").
- T-100ITNL Factory Mutual approved for fire protection service (1/2" - 2").