Insulation Rip cord Jacket

RoHS



PRODUCT SPECIFICATIONS

Part Number: HT202-02556 20 AWG/2 Conductor Thermostat Cable Solid

COMPLIANCE				
RoHS		YES		
UL Listed		YES		
NEC		YES		
CERTIFICATIONS				
UL 13, Power Limited Circuit Cable		UL 1685 Vertical Tray		
UL Listed Type CL2R		NEC Article 725	NEC Article 725	
PHYSICAL SPECIFICATIONS	5			
Conductor Material		Solid Bare Copper		
Conductor Size		20 AWG		
Number of Conductors		2		
Conductor Diameter (in.)		.031		
Insulating Material Type		Polypropylene		
Insulation Diameter (in.)		0.049		
Insulation Nominal Thickness (in.)		0.008		
Number of Insulations		2		
Insulation Color Code		Red, White		
Jacket Material Type		PVC		
Jacket Color		Brown		
Jacket Diameter (in.)		0.136		
Jacket Nominal Thickness (in.)		0.016		
Jacket Flame Rate		CL2R	CL2R	
Cable Weight (lb/500 ft)		5.75		
Ripcord		Nylon		
Sunlight Resistant		YES		
PROPERTIES		PART NUMBER	LENGTH	
TEMPERATURE RATING	-20 to 60° C	HT202-02556	500 ft Plastic Spool	
OPERATING VOLTAGE	300 Volts max.	Cross Section:		
CAPACITANCE	22 pf/ft nom.			
CHARACTERISTIC IMPEDANCE	100 Ohms nom.			
DC RESISTANCE	10.3 Ohms/M' at 20° C	Conductor		
FLAME RATING	UL 1685 Vertical Tray		Conductor	

NOTE: TECHNICAL SHEETS ARE SUBJECT TO CHANGE WITHOUT NOTICE.